

Safety data sheet
according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE
- **Article number:** 89053 (21-50310-2271)
- **Relevant identified uses of the substance or mixture and uses advised against -**
- **Application of the substance / the mixture** Bitumen coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - JENOLITE UK LTD , 1 Albone Way Biggleswade Beds, SG18 8BN
- **Further information obtainable from:**
 - sales@jenolite.com
- **Emergency telephone number:**
 - During normal business hours: Tel: +44 (0) 1234 924 794

SECTION 2: Hazards identification

- **Classification of the substance or mixture**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS09

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene)

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 1)

- P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **Mixtures**

· **Description:** Mixture of synthetic rubbers, resins, fillers and solvents

· **Dangerous components:**

EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	25-<50%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	0.1-<1%

· **Additional information:**

The text of the hazard statements mentioned here can be found in chapter 16.

The application of a TWD (Tactile Warning of Danger) is mandatory if this product is offered on the consumer market. Please note that the TWD is part of the packaging and not of the classification.

SECTION 4: First aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 2)

SECTION 5: Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Water haze
 - Fire-extinguishing powder
 - Carbon dioxide
 - Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Prevent seepage into sewage system, workpits and cellars.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

64-17-5 ethanol	
WEL	Long-term value: 1920 mg/m ³ , 1000 ppm

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 3)

· DNELs		
Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene)		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m3 (Consumer)
		2035 mg/m3 (Worker)
Reaction mass of ethylbenzene and xylene		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Aigu-systémique	174 mg/m3 (Consumer)
		289 mg/m3 (Worker)
	DNEL Acute-local	289 mg/m3 (Worker)
	DNEL Long term-systemic	14.8 mg/m3 (Consumer)
		77 mg/m3 (Worker)
	DNEL Long term-local	174 mg/m3 (Consumer)
		221 mg/m3 (Worker)

· PNECs	
Reaction mass of ethylbenzene and xylene	
PNEC Freshwater	0.327 mg/l (Unfind)
PNEC Marine water	0.327 mg/l (Unfind)
PNEC Freshwater sediment	12.64 mg/l(dry weight) (Unfind)
PNEC Soil	2.31 mg/kg (Unfind)
PNEC Sewage Treatment Plant	6.58 mg/l (Unfind)
PNEC Marine water sediment	12.64 mg/l(dry weight) (Unfind)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

General ventilation

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· **Hand protection**

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 4)

- **Eye/face protection**

Safety glasses



Tightly sealed goggles

- **Body protection:**

Use protective suit. (EN-13034/6)

Fully skin-covering anti-static, chemical- and oil-resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

- **Environmental exposure controls** Use an appropriate container to avoid environmental pollution.

SECTION 9: Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Fluid

- **Colour:**

According to product specification

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

106-140 °C (Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene))

- **Flammability**

Highly flammable.

- **Lower and upper explosion limit**

- **Lower:**

0.7 Vol %

- **Upper:**

7 Vol %

- **Flash point:**

2 °C

- **Ignition Temperature**

256 °C (Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene))

- **pH**

Mixture is non-polar/aprotic.

- **Viscosity:**

- **Kinematic viscosity**

Not determined.

- **Dynamic at 20 °C:**

8000 mPas

- **Solubility**

- **water:**

Not miscible or difficult to mix.

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Vapour pressure at 20 °C:**

30 hPa

- **Density and/or relative density**

- **Density at 20 °C:**

1.05 g/cm³

- **Relative density**

Not determined.

- **Vapour density**

Not determined.

- **Other information**

- **Form:**

Viscous

- **Important information on protection of health and environment, and on safety.**

- **Ignition temperature:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Organic solvents:**

50.1 %

- **Solids content:**

45.0 %

- **Evaporation rate**

Not determined.

- **Information with regard to physical hazard classes**

- **Explosives**

Void

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 5)

· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene)

Oral	LD50	>5000 mg/kg (Rat)
	LD50	>8 ml/kg (Rat)
Dermal	LD50	>3100 mg/kg (Rat)
Inhalative	LC50 (4h)	>23.3 mg/l (Rat)

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523 mg/kg (Rat)
Dermal	LD50	12126 mg/kg (Rabbit)
Inhalative	LC50 (4h)	29000 mg/l (Rat)

- **STOT-single exposure** May cause drowsiness or dizziness.
- **Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 6)

*

SECTION 12: Ecological information

· Toxicity

· Aquatic toxicity:

Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (< 0.1% benzene)

NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3 mg/l (Daphnia magna)
EL50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)

Reaction mass of ethylbenzene and xylene

NOEC	1.3 mg/l (Fish)
NOEC (7 days)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (algae)
NOEC (28 days)	16 mg/l (Bacteria)
LC50 (96h)	8.9-16.4 mg/l (Pimephales promelas)
EC50 (48h)	3.2-9.5 mg/l (Daphnia magna)

- **Persistence and degradability** Not easily biodegradable
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

*

SECTION 13: Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

*

SECTION 14: Transport information

· UN number or ID number	
· ADR, ADN, IMDG, IATA	UN1139
· UN proper shipping name	
· ADR, ADN	UN1139 COATING SOLUTION, ENVIRONMENTALLY HAZARDOUS
· IMDG	COATING SOLUTION, MARINE POLLUTANT
· IATA	COATING SOLUTION

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 7)

· **Transport hazard class(es)**· **ADR, IMDG**· **Class**

3 Flammable liquids.

· **Label**

3

· **ADN**· **ADN/R Class:**

3 Flammable liquids.

· **IATA**· **Class**

3 Flammable liquids.

· **Label**

3

· **Packing group**· **ADR, IMDG, IATA**

III

· **Environmental hazards:**Product contains environmentally hazardous substances:
Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic (<
0.1% benzene)· **Marine pollutant:**

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** -· **EMS Number:**F-E,S-E· **Stowage Category**

A

· **Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

E

· **Remarks:**

visceuze vloeistof / viscous liquid (cf. ADR 2.2.3.1.4)

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Remarks:**

viscous liquid (cf. IMDG 2.3.2.2)

· **UN "Model Regulation":**UN 1139 COATING SOLUTION, 3, III,
ENVIRONMENTALLY HAZARDOUS

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 8)

*

SECTION 15: Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Breakdown regulations:

Class	Share in %
NK	50-<75

· VOC-CH 50.15 %

· VOC-EU 526.6 g/l

· Danish MAL Code 5-3

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

· Contact: ing. J. Sleumer

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31. (2020/878)

Printing date: 27.11.2023

Version: 22 (replaces version 21)

Revision: 27.11.2023

Trade name: JENOLITE STONECHIP PROTECTION SCHUTZ - GREY - 1 LITRE

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 MAL-Code: Måleteknisk Arbejdshygienisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered. ***

GB